Volume II Section 2.0.3 Revision 4 April 1, 2000 Page 1 of 20

2.0.3 **DOCUMENTATION**

2.0.3.1 GENERAL INFORMATION

Documenting analyzer maintenance, analyzer operational checks, calibration dates, and other activities which may affect the data quality are important facets of an operator's job. Two documents are used by the station operator to assist in the documentation: a station log and equipment relocation notifications. A brief summary of the use of these documents follows.

2.0.3.2 STATION LOG

A monitoring station log book must be maintained at each monitoring site. Conditions which may influence the data must be recorded in the log book. Some examples are: nearby construction, abnormal traffic patterns, or alterations to the sampling train (probe or equipment change). A current copy of the sampling site report should be contained in the station records. The site report must be kept up-to-date. Any time a parameter (instrument, site location, probe, etc.) is modified or changed the site report should be revised and a copy forwarded to the immediate supervisor. An example of a completed site report is attached to this section (Figures 2.0.3.la, 2.0.3.lb, 2.0.3.1c, 2.0.3.1d.). The station log also serves as a permanent record of the acceptance test, routine maintenance, repairs, and calibrations performed on an instrument and travels with that instrument at all times. All routine maintenance, repairs, calibrations, installation dates, or other pertinent information should be logged and dated as they occur. Thus, the station log serves as a permanent record of instrument performance.

2.0.3.3 <u>EQUIPMENT RELOCATION NOTIFICATION</u>

In general, equipment relocation notifications (ERNs) are required when equipment having an ARB property number (e.g. analyzer) or related equipment (printed circuit board, vacuum pump, source lamp) are relocated or repaired. In addition, an ERN is required when a compressed hydrogen gas cylinder is relocated. For other compressed gases, see Section 2.0.3.5.

The ERN contains spaces for original location, destination, station numbers, ARB numbers, parent ARB numbers, instrument description, manufacturer and model number, parameter, serial numbers, repair information, job number, and comments.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 2 of 20

The extra "Station No./Date" block in the "Destination" row of the ERN is used to enter interim station location information. Before the equipment is shipped from the lab in Sacramento, the station number of the destination will be entered in the leftmost "Station No." block and the white original removed. If the equipment is shipped to an interim location and field air monitoring personnel move it again to its final location, the field personnel involved will enter the final destination station number and date in the right "Station No." block and send the yellow copy to the lab for processing without filling out a second tag. When lab personnel receive the yellow copy, the new location information will be entered into the computer.

The "Job No." block will be used for Instrumentation Sub-Section internal workload control, and the "Repair Information" block will be completed by laboratory personnel when necessary.

When completing an ERN for an instrument or component part being sent to the Lab for repair, please describe the malfunction in as much detail as possible in the "Comments" section of the tag. A complete description of the malfunction will help Instrumentation Laboratory staff to duplicate and repair the malfunction.

Attach the complete ERN, with all copies and the original, to the component part or instrument to be shipped so Instrumentation Laboratory personnel can process the entire tag. The original will be left on the unit for the repair technician who needs the legible original of the description of the malfunction, and the yellow copy will be used to enter the location information into the computer.

Filling out ERNs completely and accurately whenever equipment is moved is very important, because it provides information as to the location of valuable ARB property and provides a detailed description of any malfunctions or operational characteristics of the equipment being shipped.

1. Relocation of Major Assemblies - Whenever equipment with an ARB-assigned property number is relocated, an ERN must be completed. This includes relocating instruments between air monitoring stations, between the shop and air monitoring stations, and between the ARB and instrument vendors. Multi-module instruments which have separate ARB numbers require separate ERNs. Figure 2.0.3.2 is an example of a properly completed ERN for a major assembly.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 3 of 20

- 2. Relocation of Components or Sub-assemblies The procedure for completing an ERN for relocation of components or subassemblies is identical to that for major assemblies, with one exception. The lone exception is that the ARB property of the major assembly in which the component or subassembly will be used must be entered in the block labeled "Parent ARB No." The "Parent ARB No." must be specified when requesting components or sub-assemblies from the shop. Clearly indicate in the "Comments" section the reason for returning any component or sub-assembly to the shop. Figure 2.0.3.3 is an example of a properly completed ERN for a subassembly.
- 3. Routing of Equipment Relocation Notifications The hard copy of the ERN must accompany the item being relocated. The three soft copies of the ERN should be routed to the Air Quality Monitoring Support Section in Sacramento, according to the procedure delineated by the supervisor of the respective units. The ERN's are screened for correctness, and then forwarded for inclusion in the station files (white copy), instrument files (yellow copy), and the ARB property records (pink copy).

2.0.3.4 SITE IDENTIFICATION REPORT

INSTRUCTIONS FOR COMPLETING THE SITE IDENTIFICATION REPORT

This report should be submitted to the Air Resources Board (ARB) whenever a new site is established or when any parameter contained in the report is changed or modified.

When submitting changes for existing sites, only the "Site Name" and "Site Number", as assigned by the ARB, need be entered. Any other information entered on the form should only be those items that have changed. Each time a new report is submitted, include an 8-1/2" x 11" section of a U.S. Geographical Survey (or local street) map indicating the site location and photographs of the four quadrants surrounding the site (indicate the quadrant on the photograph).

Tables and additional guidelines for coding and submitting air quality data to the ARB's Aerometric Data System can be found in the ARB publication "User's Manual: California Aerometric Data System".

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 4 of 20

The following are guidelines for filling in the requested information:

HEADING:

In the space provided on the top of the report, enter your name and the date. Indicate by an "X" in the appropriate block whether this report is a new submission or a revision to a previously submitted Site Identification Report.

SITE IDENTIFICATION:

Agency Responsible for Site - Enter the name of the agency responsible for maintenance, rental and equipment at the site.

Site Location - Enter the names of the air basin and county in which the site is located.

Geographical Coordinates - Enter <u>either</u> the longitude and latitude or the UTM (Universal Mercator) coordinates.

Longitude - Enter degrees, minutes and seconds of longitude for this site as indicated. Make no entry if UTM system for site location is used.

Latitude - Enter degrees, minutes and seconds of latitude for this site as indicated. Make no entry if UTM system for site location is used.

UTM Z one - Enter the two-digit UTM zone code.

Easting Coordinate - Enter the easting UTM coordinate for this site (in meters) from the appropriate section of a UTM map. This entry must be right justified with leading zeros* and should be accurate to the nearest meter. UTM coordinates are automatically calculated if longitude and latitude have been entered.

Northing Coordinate - Enter the northing UTM coordinate for this site (in meters) from the appropriate section of a UTM map. This entry must be right justified with leading zeros* and should be accurate to the nearest meter.

*If less than five digits enter the values in the rightmost boxes, filling the remaining boxes with zeros.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 5 of 20

SITE DESCRIPTION:

Location - Enter an "X" in the box that best describes the location of the site.

Dominating Influence - Enter an "X" in the box that best describes the dominating influence within a one-mile radius of samplers at the site.

Traffic Type - Enter an "X" in the box that best describes the predominant type of traffic around the site.

Estimated Traffic Volume - Enter the estimated traffic volume on the street nearest the site (vehicles per day) in boxes 20 through 26. This entry must be right justified with leading zeros*.

Estimated City Population - If the population of the area (city or town) in which the site is located is 2,500 or more, enter the estimated city population in boxes 27 through 34. This entry must be right justified with leading zeros*. If the site is located outside the jurisdictional limits of an area of this size, enter all zeroes in these boxes. If the population is less than 2,500, leave the boxes blank.

Temperature Controlled Area - Enter an "X" in the appropriate box in answer to the question: "Is the area where the instruments are located temperature controlled at 25 °C +/- 5 °C? "

Elevation of Site Instruments Above Ground - Enter the elevation (to the nearest tenth of a meter) of the site above ground level. The site is the area in which the air monitoring instruments are located. If the air monitoring instruments are not all located within a vertical distance of five meters of each other, enter a "9999" in the space provided. Then enter the respective elevation information in the "Comments" block. (For example, SO2 sampler at 20 meters, NO bubbler at 30 meters, etc.)

Elevation of Ground Above Mean Sea Level - Enter the ground elevation of the instruments to the nearest tenth of a meter above mean sea level following the same criteria as set forth above.

SITE LOCATION:

Site Address - Enter the full address of the site (number, street, city, and state). For areas that do not have a street address, enter a descriptive phrase such as the

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 6 of 20

name of a building or area that will adequately locate the site. Limit your entry to 37 characters using reasonable abbreviations if necessary (e.g. "Mt." for mountain, "Ct." for court, etc.).

Zip Code - Enter the five-digit postal zip code assigned to the geographical area in which the site is located. If necessary, refer to a copy of the National Zip Code Directory for the appropriate code.

COMMENTS:

Enter appropriate comments which could help characterize the site. Limit the combined total number of characters to 120. Applicable comments might be as follows:

Site within two blocks of heavy construction

Site on building adjacent to main street of town

Organization site code if different from ARB code

Names of other agencies whose samplers are at the site

2.0.3.5 <u>INSTRUCTIONS FOR COMPLETING THE PROBE/SAMPLER</u> IDENTIFICATION REPORT

This report must be submitted to the ARB: 1) whenever a new probe or individual sampler is installed; and 2) whenever the dimensions, materials, or the location of the probe or individual sampler changes. Physical replacement of a sampler does not require a new Probe/Sampler Identification Report, provided the physical dimensions, flowrate, and other pertinent characteristics of the probe are not changed.

When submitting changes to existing probes or sampler, only the "Site Name" and "Site Number", as indicated on the initial report need be entered. Any other information entered on the report will be treated as changes to the originally submitted report.

Tables and additional guidelines for coding and submitting air quality data to the California Air Resources Board's (ARB) Aerometric Data System can be found in the ARB publication "User's Manual: California Aerometric Data System".

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 7 of 20

HEADING:

In the space provided on the top of the report, enter your name and the date. Indicate by an "X" in the appropriate block whether this report is a new submittal or a revision to a previously submitted Probe/Sampler Report.

SITE IDENTIFICATION:

Site Name - Enter the ARB assigned site name as designated on the appropriate Site Identification Report, which is submitted for the site where the probe or sampler is located. The sampling site information must be exactly the same as that presented on the Site Identification Report.

Site Address - Enter the address of the site (number, street, city) as shown on the Site Identification Report submitted for the site where the probe or sampler is located.

Site Location - Enter the names of the Air Basin and county where the site is located.

PROBE/SAMPLER IDENTIFICATION:

Sampler Category - Enter an "X" in one box next to the category where the probe or sample is used.

Probe/Sampler Identification Code - Select a designation (01, AZ, 2B, etc.) which will uniquely identify the probe or sampler described on the form. The code must correspond to the code entered on the accompanying schematic diagram.** (See note below.) All subsequent references to this probe or sampler shall be by this code.

Operating Period - Enter <u>either</u> the initiation or termination date of probe or sampler operation at the site. If the probe or sampler is physically relocated within the site or established at the new site, the appropriate reports must be submitted, which terminate the operating period of the old probe or sampler and initiate the operating period of the new or relocated probe or sampler. A probe or sampler whose operating period has been terminated may be reinstated utilizing the "Probe/Sampler Identification Code" previously assigned. However, the physical characteristics of the probe or sampler, designated when the code was originally assigned, must be the same. The entries must be right justified with leading zeros.***

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 8 of 20

Air Intake/Wind Sensor/Sampler Height Above Ground - Enter the height, in meters, of the probe (air intake of wind sensor) or sampler above the ground. This entry must be right-justified with leading zeros.***

Horizontal Distance of Air Intake/Wind Sensor/Sampler from Nearest Street - Enter the horizontal distance, in meters, of the probe or sampler from the nearest street. This entry must be right-justified with leading zeros.***

Distance of the Air Intake/Wind Sensor/Sampler Above/Below Roof Level - If located on a building, enter the distance, in meters, of the air intake, wind sensor, or sampler above or below the roof line. If the air intake, wind sensor, or sampler is below the roof of the building but not on the ground, enter a "2" in the box labeled "ABOVE/BELOW". If the air intake, wind sensor, or sampler is located on the ground or above the roof line, leave the box labeled "ABOVE/BELOW" blank. In all cases, the location of the air intake, wind sensor, or sampler must pass the Obstruction Test as defined later under "Obstruction Test". If found to be obstructed, the appropriate entries must be made on the report. This entry must be right-justified with leading zeros.***

Direction of Nearest Street from AIR Intake/ Sampler - Enter an "X" in the box next to the direction of the nearest street from the air intake or sampler. In the case where the air intake or sampler has streets which are equally distant in two directions (i.e., one street to the north and one to the west), give the direction of the most heavily traveled street.

Obstruction Test - If the air intake, wind sensor, or sampler is obstructed as defined below*, enter the type of obstruction, direction, and distance (in meters) as indicated.

CONTINUOUS SAMPLING AND TAPE SAMPLER:

All numerical entries in this section must be right justified with leading zeros.***

Probe Inside Diameter - Enter, in millimeters, the inside diameter of the probe.

Probe Air Flowrate - Enter, in liters per minute, the flowrate of the sample air in the probe.

Total Probe Length - Enter, in meters, the length of the probe from the air intake to the distribution manifold or instrument inlet.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 9 of 20

Air Sample Residence Time - Enter, in seconds, the residence time of the air sample in the probe taken from the air intake to the distribution manifold or instrument inlet (see calculation formula on next page).

Distance of Air Intake from Wall - If the air intake is below the roof line and extends out from a building, enter the horizontal distance, in meters, of the air intake from the wall. If the air intake does not extend from the side of a building but is below the roof line of the building, apply the obstruction test, and recordidentifying information noted above.

How Many Instruments Sample from this Probe - Enter the number of continuous air monitoring instruments which draw their sample air from this probe.

If More than One Instrument, Is a Distribution Manifold Used? - Enter an "X" in the appropriate box. If the Yes box is checked, fill in both the "Distribution Manifold Diameter" and the "Distribution Manifold Length" as indicated below.

Distribution Manifold Inside Diameter - Inside diameter, of main run, enter diameter in millimeters.

Distribution Manifold Length - Enter the length, in meters, of the main run of the distribution manifold.

Orientation of Air Intake - Enter an "X" in the box next to the item that best describes the orientation of the air intake.

Probe Material - Enter an "X" in the box that identifies the composition of the probe. If the "Other" box is checked, specify the probe material in the space provided. Note that the only acceptable sampling probe material is borosilicate glass or FEP Teflon (40 CFR Part 58, Appendix E).

Distribution Manifold Material - Enter an "X" in the box that best describes the material the distribution manifold is made of. If no distribution manifold is used, do not check any boxes. If the "Other" box is checked, specify the probe material in the space provided.

CALCULATION OF TOTAL RESIDENCE TIME:

Total residence time is a sum of the probe, manifold, and manifold to instrument residence times.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 10 of 20

Probe - Probe residence time in seconds (sec) equals the cross-sectional area of the probe in square millimeters (mm) times the total length of probe in meters (m) divided by the total flow rate in liters per minute (lpm), and is given by the formula shown below:

Manifold - Manifold residence time in seconds (sec) equals the cross-sectional area of the manifold in square millimeters (mm) times the total length of the manifold in meters (m) divided by the total flow rate in liters per minute (lpm), and is given by the formula shown below:

Manifold to Instrument - Manifold to instrument residence time in seconds (sec) equals the cross-sectional are of the manifold in square millimeters (mm) times the total length of the tubing from the manifold to each instrument in meters (m) divided by the flow rate in liters per minute (lpm) for the instrument, and is given by the formula shown below:

 $t = (\pi(d)^2 \times L \times .015) / Q$

where

t = residence time, sec.

 $\pi = 3.14 \text{ etc.}$

d = probe or manifold inside diameter, mm

L = probe or manifold length, m

Q = flow rate, 1/m .015 = conversion factor

or t = 1.0677 x L/Q for 3/16" ID or 4.76 mm diameter and t = 1.9002 x L/Q for 1/4" ID or 6.35 mm diameter and t = 7.6008 x L/Q for 1/2" ID or 12.7 mm diameter

*An air intake, wind sensor or sampler is obstructed if an imaginary line extended 30° up from the horizontal and rotated 360° intersects any obstruction within 30 meters.

**Each time a Probe/Sampler Identification Report is submitted, include a dimensioned schematic showing: a) the configuration of each probe and distribution manifold; b) the location of each individual sampler; c) the "Probe/Sampler Identification Code" assigned to each probe or sampler; d) the pollutants sampled from each probe or sampler; and e) obstructions which fall within the constraints of the obstruction test.

***If less than five digits enter the values in the rightmost boxes, filling the remaining boxes with zeros.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 11 of 20

NOTE: ARB requires a sample residence time of ten seconds or less for all SLAMS or NAMS. Also, the Probe/Sampler Report worksheet is currently being revised to include the calculation of the manifold residence time and the manifold to instrument residence time. The residence time should always be calculated

2.0.3.6 <u>INSTRUCTIONS FOR COMPLETING THE POLLUTANT/PROJECT</u> IDENTIFICATION REPORT

This report must be submitted whenever the project, agency pollutant, collection/analysis method, reporting units, instrument number, or the probe/sampler identification code starts or changes for any air monitoring activity at a site. When completing a new report, only fill in the requested information in the section entitled "To Be Completed By the Reporting Agency" (Right side).

When submitting changes to an existing air monitoring activity, complete only the "Site Identification Code", and "Site Name", (as assigned by the ARB) in the section entitled "For ARB use only" and the specific changes on the right side. Any other information entered on the form will be treated as changes to the originally submitted report.

Tables and additional guidelines for coding and submitting air quality data to the California Air Resources Board's (ARB) Aerometric Data System can be found in the ARB publication "User's Manual: California Aerometric Data System".

HEADING:

In the space provided on the top of the report, enter your name and the date. Indicate by an "X" in the appropriate block whether this is a new submittal or a revision to a previously submitted Pollutant/Project Identification Report.

PROJECT IDENTIFICATION SECTION:

Purpose of Sampling - Enter the purpose for the pollutant monitoring (abbreviate) described later in this report. If there is more than one project at a site, separate reports must be submitted. For example: The ARB is conducting parallel monitoring for ozone with an APCD. Two reports must be submitted: one describing the ARB's project as a special study and another describing the APCD's project as ambient monitoring.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 12 of 20

Site Name - Enter the ARB assigned site name as designated on the Site Identification Report submitted for the site. The sampling site information must be exactly the same as that presented on the Site Identification Report.

Site Address - Enter the address of the site (number, street, city) as shown on the Site Identification Report submitted for the site.

Site Location - Enter the names of the Air Basin and county in which the site is located.

Agency Responsible for Data Submittal - Enter the name of the agency responsible for collecting and submitting the data to the ARB.

POLLUTANT SAMPLING INFORMATION SECTIONS (SPACE PROVIDED FOR TWO POLLUTANTS):

Pollutant Sampled - Enter the name of the pollutant being monitored as part of the project described under "Purpose of Sampling" (i.e., Sulfur Dioxide (SO_2), Oxidant (O_x)).

Collection/Analysis Method - Enter the sampling method used to monitor the pollutant described under, "Pollutant Sampled" (i.e., chemiluminescent, pulsed fluorescence, flame photometry, etc.).

Reporting Units - Enter the units (ppm, pphm, ug/m³, etc.) in which the data is to be reported.

Instrument Manufacturer - Enter the name of the manufacturer of the air monitoring instrument (abbreviate).

Model No. - Enter the manufacturer's model number for the air monitoring instrument.

Sampling Period - Enter either the initiate or terminate data for monitoring of the pollutant described under "Pollutant Sampled". The entries must be right-justified with leading zeros. If any of the entries made previously in this section change, a revised report must be submitted. The revised report should: 1) terminate monitoring of the pollutant under the characteristics in existence prior to the change, and 2) initiate monitoring of the pollutant under the new characteristics established as a result of the change.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 13 of 20

Instrument Property Number - Enter the last five digits of the air monitoring instrument property number. If the property number contains less than five digits, values must be right-justified with leading zeros.*

Probe/Sampler Identification Code - Enter the Probe/Sampler Identification Code assigned to the probe or sampler used in monitoring the pollutant described under "Pollutant Sampled" and indicated on the Probe/Sampler Identification Report. Each air monitoring instrument (and pollutant) at a site is referenced to a probe or to an individual sampler by this code. If an identification code changed due to relocation or alteration of the characteristics of a probe or sampler at a site, a revised pollutant/project identification report must be submitted. This report should terminate the operation of the instrument under the old code and initiate its operation under the new code.

*If less than five digits, enter the values in the rightmost boxes, filling the remaining boxes with zeros.

2.0.3.7 CERTIFICATE OF ANALYSIS

A Certificate of Analysis is required for all cylinders (except hydrogen) to track their location. The destination of each cylinder is entered on the top (white) section of the Certificate of Analysis form when the cylinder is shipped. The "Return Information" section (bottom) of the form is completed on the hard copy by field air monitoring personnel when the cylinder is returned to the lab. Figure 2.0.3.4 is an example of a properly completed Certificate of Analysis.

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 14 of 20

CALIFORNIA AIR RESOURCES BOARD Technical Services DIV., EDP Management P.O. Sox 2315 Secremento, CA 95912 STE IDENTIFICATION REPORT

ATTACH AN 855" × 11" PORTION OF A U.S. GEOLOGICAL SURVEY FOR LOCAL STREET, MAP INDICATING SITE LOCATION. INCLUDE PHOTOGRAPHS OF THE POUR GUADRANTS SURROUNDING THE SITE.

PORT COMPLETED BY:	DATE THIS REPORT IS AMENDS A PREVIOUS REPO
	FOR ARB USE ONLY
ACTION CARD ID	SITE NAME (ARB Assigned)
SITE NUMBER	TO BE COMPLETED BY REPORTING AGENCY
COUNTY TYPE SITE	AGENCY RESPONSIBLE FOR SITE
	SITE LOCATION (AIR BASIN, COUNTY)
	one countries on the country
	GEOGRAPHICAL COORDINATES (ENTER LONGITUDE & LATITUDE OR UTM COORD.)
	LONGITUDE DEG. LATITUDE MIN. SEC.
	UTIM ZONE FASTING COORD. INSTERS) NORTHING CODRD. INSTERS
ACTION CARD ID	CHECK ONE ITEM IN EACH CATEGORY THAT PERTAINS TO THE SAMPLING SITE. LOCATION
	1. CENTER CITY 2. SUBURBAN 3. SURAL 4. SEMOTE
PUNCH COL. 3-9 AS SHOWN ABOVE	DOMINATING INFLUENCE 1. INDUSTRIAL 2. RESIDENTIAL 3. COMMERCIAL 4. VEHICULAR
ENVIRONMENT TRAFFIC	
	S. NEAR URBAN S. AGRICULTURAL 7. SECREATIONAL 9. OTHER ISPECIFY
ELEV. ABOVE GND.	TRAFFIC TYPE 1, RESIDENTIAL 2, INDUSTRIAL 3, FREEWAY 4, ARTERIAL
	6. COMMERCIAL G. GYHER ISPECIFY
ELEV. ABOVE MSL CONTROL	RET. TRAFFIC VOLUME ON NEAREST STREET (VEH./DAY) 20 21 22 24 25 25 27 28 28 28 28 28 28 28 28 28 28 28 28 28
	IS THE AREA WHERE AIR MONITORING INSTRUMENTS ARE LOCATED 1, YES 2, NO
	ELEVATION OF SITE (INSTRUMENTS) ABOVE MEAN SEA (METERS) ELEVEL (WETERS)
ACTION CARD ID	SITE ADDRESS: (NUMBER, STREET (13-34)
Eq.	CITY (36-47) STATE (48-491) . (50-64) ZIP COD
PUNCH COL. 3-9 AS SHOWN ABOVE	CLOSE PARENTS IN THE STREET OF STREET AND LABOUR AND LA
ACTION CARD ID	(13-72) COMMENTS (ENTER COMMENTS THAT WILL HELP IDENTIFY THE SITE SUCH AS LANDMARK
- Car	TERRAIN FEATURES, ETC.)
PUNCH COL. 3—9 AS SHOWN ABOVE ACTION CASD ID	(13-72)
PUNCH COL. 3-9 AS SHOWN ABOVE	
R MONITORING:	ARE PROCESSING (INITIALS, DATE) RECEIVED: LOGGED:

TSD-4 (REVISED 11/77)

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 15 of 20

CALPORNA ARE RESOURCES BOARD MONITORING ARE LABORATORY DIVISION ARE BRAILTY SURVEILLANCE BRANCH PROPER AS AN PLET THE PLATFORM REPORT

THIS REPORT IS TO BE COMPLETED WHEN INSTALLING OF RELOCATING ARY PROBE CAR SAMPLING SYSTEM", WHILD SERISOR, OR INCOMPANIAL SAMPLING HE WAY, TAPE SAMPLING OF RELOCATING AND STREET OF STRE

COMPLETO OF	DIRPRIGHATION OF FACE PROBE AND DISTRIBUTION MANIFOLDS. ON THE LOCATION OF EACH MOVIMULAL SAMPLER IN RESPECT TO STREET SAMPLER AND TO MALOW, INSERTIFY, ON THE SOMEWAIN, THE PROBE OF SAMPLER IS, COOK AND THE POLICITARY'S SAMPLER PROBE OF SAMPLER. [THE SETTING.]
	DATE THE REPORT IN PART A NEW ON REJECTED AMERICE A PREVIOUS REPORT
FOR ARB USE ORLY	TO BE COMPLETED BY REPORTING AGENCY
ACTOR . GARO IS	SITE MAKE AS ASSESSED BY THE AND
COUNTY TYPE 34TE	DECE ONE SAMPLES CATEGORY FOR WHICH THE PROOF OF SAMPLES SPECHED BLUCK IS USED.
PRODE/SAMPLER GOOD SAMPLER CATEGORY	1. COMPRESSURE 1. TAPE SAMPLER 1. ACRO DEPOSITION 1. TERM SAMPLER 1. TERM SAMPLER
13 W 16	FORTER THE PROBLESAMPLER REINTURCATION CODE (SEE INSTRUCTION NUMBER ONE ABOVE), CODE MUST CONNESPOND TO THE RESPECTIVE CODE DESIGNATED ON THE ATTACHED SCHOMATE (SEE INSTRUCTION NUMBER 2 ANOVE).
G G	OPTIVATES PRIVATE STREET SET TERMINATE OF THE SET OF TH
PUNCH COL. 3-14 AS SHOWN ABOVE OPERATION OPERA	YEAR MONTH WONTH MONTH PACTERS. 22 25 34 25 29 27 38 28 30 31 32 33 34 28 28 28
	DISTANCE OF ARE WITAKE/WHICH SERBOA/SAMPLER ABOVE/BELOW ROOF LEVEL. IF BELOW ROOF LEVEL, SITTER A "2" ME BOX LABBLED "ABOVE/BELOW": STREEWISE LEAVE THE BOX SEARCE.
BR. MARKET BRIT, MARKING,B. ETRET BY VEL MINES -1-	30 36 26 40 41
ORGETATION DES MATERIAL DES	S. SOUTH 6. SOUTHWEST 7. WEST 6. RORTWAST
18 21 20 21 21 21 21 21 21 21 21 21 21 21 21 21	ALD OF A LIME COTTENING NOT OF FORCE FOR INTERCENT AT THE ARE NETABLE WHIRE SERVING SERVING SAMPLES AND RETAINED SHIP INTERCECTS ANY DECORATION WITHIN MICHAEL WHILE SERVING S
† -0	
NAME AND ASSESSED ASSESSEDA	TACE
HORIZONTAL	COMPLETE FOR CONTINUOUS SAMPLING PROBES AND TAPE SAMPLERS ONLY PROBE MISCE PROBE AND TRULE PROBE AND TAPE SAMPLERS ONLY
#00 MOOF	CALAMETER PLOYMATT LISSETS PRODUCES THAT AND PRO
la DISTRIBUTION ALL	THE COLUMN
DISTRIBUTION MANIFOLD	OMERITATION OF AN RETAIN (CHICK ONE) 1. VESTICAL 2. BOWN 1. HONOCONTAL PROMI WATERAL (CHICK ONE)
*	TRT . TIPLES . SHARE . SPECIFF.
TO INSTRUMENTS	I. TUNIN 1 SAAS 1 STORM

Figure 2.0.3.1b
Probe/Sampler Identification Report

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 16 of 20

CALIFORNIA AM SESSONCES BRAINS MONITORING AND LABORATORY SEVESION AIR OBJALTY SURVELLANCE SHARCH POLLUTART/PROJECT IDENTIFICATION REPOR

Mark County and an	The same of the second of the			
EPOST COMPUTED IN:	DATE THE REPORT SOMETOWER AMERICA A PART OF THE PART O	IS REPORT		
FOR ARB USE DRLY	TO BE COMPLETED BY REPORTING AGENCY			
ACTION CAMO ID	THE INFORMATION PRESENTED BELOW WILL BE USED TO ESTABLISH THE CATEGORY (PROJECT) I SPECIFED POLITICALLY WILL BE ENTENED. PURVISE OF SAMPLING LIMITED WORTHWAY. SPECIAL STUDY, ETC.)	NTO WHICH DATA FOR		
SITE IDENTIFICATION CODE				
3 4 5 6 7 6 8 16 11 12	SITE NAME AS ASSESSES BY THE AMB			
ARKS IDENTIFICATION CODE STATE DOUBTY SITE MERCY	STE LOCATION JUN BASIN, COLUMN			
13 14 15 14 17 16 19 29 21 22	ASSECT PLOPOROBLE FOR GATA SUBMITTAL			
ACTION CAME ID	POLISTANT SAMPLING INFORMATION ENTERED BELOW PERTAINS TO THE "PENG-OSE OF SAMPLIN POLISTANT SAMPLED	S" DESCRIBED ABOVE.		
PUNCH COL 3-12 AS SHOWN ABOVE	COLLECTION/AMA/YOR MITHOD	REPORTING LINETS		
ARB POLLUTANT CODE				
PRILITRATE METRICO LARTE	SAMPLING PERSON DISTRICT OFFICE METHATS ON TERMINATED DATES: SAMPLING PERSON DISTRICT OFFICE METHATS ON TERMINATED DATES:	MARKET NO.		
12 14 75 18 17 16 19 20 21	OUT THAT LIAT ING	DIGITE		
Take SAMPUNG SAMPUNG	TEAM MONTH YEAR MENTH YEAR MENTH 28 29 39 31 32 23 34 36 36 37	34 29 49		
PROJECT SALES	ENTER THE PROBLESAMPLES CONTURCATION CODE ASSESSED TO THE PROBE OR SAMPLES UTFLICTED IN SAMPLING FOR THIS POLLUTANT, CODE CAS SE POURS ON THE APPROPRIATE TROOSE/SAMPLES COURTERCATION REPORT. AND CORRESPONDING SCHEMATIC FOR THE STE BAMES ABOVE.	PROBLES AND LER BEST TOTAL TOTAL COOK		
ACTION CARD ID	POLISTART SAMPLING INFORMATION EXTENSES BELOW PORTAINS TO THE "PURPOSE OF SAMPLIN	E" DESCRIBED ABOVE.		
	POLUTART SAMPLE			
. PUNCH COL. 3-12 AS SHOWN ABOVE ARE POLIUTARY CODE	COLLECTION/ARALYSIS INCTIONS	REPORTING UNITS		
POULTANT METHOD UMTS.	RETRUMENT MANUFACTURES	SHOOL ML		
13 14 15 16 17 16 15 20 21	SAMPLING PERIOD GINTER STREET ARTHATE OR TERMINATE GATES SETTIMENCET PROPERTY (GINTER TIME GATE FIVE	Y MUNICIPAL DISECTED		
TIME SAMPLING MINISTRAL MALMON ACTUARY BETTURYAL PERMIS COOK MINISTRAL TIME COOK 22 23 24 26 36 12	### TILAN BADRITH TEAMBRANE DAILY YEAR BADRITH THEM BADRITH 28 29 26 31 32 23 34 36 36 37	29 .30 .42		
PUBLISH PUBLISH APPORT 41 42 43 44 45 46	ENTER THE PROBE/SAMPLER ECENTRICATION GOOD ASSIGNED TO THE PROBE OR SAMPLER UTILIZED IN SAMPLING FOR THIS POLILITANT, CODE CAR BE FOUND ON THE APPROPRIATE "PROBE/SAMPLER ECENTRICATION REPORT" AND CONNESPONDING SCHEMATIC FOR THE SITE RANGE ABOVE.	PROBLES AND EN ENTER COOK		
ARE APPROVAL (METLACS, GATE) ARE QUALITY MONITORING:	GA. ARR GRAMITY GATA:			

Figure 2.0.3.1c Pollutant Project Identification Report

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 17 of 20

CALIFORNIA AIR RESOURCES BOARD Monitoring & Laboratory Division SITE INITIATION/TERMINATION REPORT

parameters.
itoring Type ISLAMSISPMIPSD

Figure 2.0.3.1d Site Identification Report

MLD-87 (01/91)

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 18 of 20




Figure 2.0.3.2 Relocation of Major Assemblies

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 19 of 20

	EQUIPMENT RELOCA	EQUIPMENT RELOCATION NOTIFICATION	No. B	No. B- 00936
;	F Location	Station No. Date: 1/10/83	Equipment Classification—USE ONE ONLY	n-USE ONE ONLY
	001H)	04-628 By: Gardiner	Major Assembly ARB No.	No.
	1 Destination SACRAMENTO SHOP	Station No. 344—297 Date: 1/13/83 Date:		Parent 4-605
	D W	Parameter measured	Repair Information	Date Serviceable;
0	POWER SUPPLY BOHED	ВОЯКИ		Вуз
	Manufacturer Model No.	Serial or Cylinder No.		
	DASIBI	УН		
	Condition	Comments, reason for relocation, description of problem or failure	of problem or failure	Job No.
		-100 VDC measures 0V.	PIS S. J. VR.	MON TO NO SECON
0	Repair Needed Unknown	Suspect bad emitter follower Q5.	Nower QE.	1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	INSTRUCTIONS: Secure completed tag to equipment.	ag to equipment.		and and second in the second s

Figure 2.0.3.3 Relocation of Components or Sub-assemblies

Volume II Section 2.0.3 Revision 4 April 3, 2000 Page 20 of 20

	CERTII	ICATE	OF A	NALYS	IS
	TECH	INIA AIR F INICAL SE	RVICES	DIVISION	
COMPRESSED	GAS CYLI	NDER NUM	BER: _C	<u>C12817</u>	
ANALYSIS DA	TE:1 <u>/21/</u>	82 _{CYLING}	DER PRE	SSURE: 19	900
LOCATION:	ARB (AGENCY)	Modes to	50	-568	
CERTIFIED CO	188	ON(S) OF:	HA/TH	_ IN	N2
	200				GAS
		PM OF	CO		_ GAS
	127.2	PPM OF	NO	_	GAS
	62.2	PM QF	S0 ₂		_ GAS
CERTIFIED BY	_	26			
	ATION IS			CYLINDE	P
PRESSURE DR	OPS BELO	w <u>300</u> PSIG	OR A	FTER 1/	21/8:
RETURN INFOR	MATION				
REASON (V)	OTHER _		RECERTI	FICATION .	
RETURN DATE	:	CYLIN	DER PRE	SSURE: _	

67057-119 1 M DUP - CSP